

Problem #90

Originator: Hubert Comon, Manfred Schmidt-Schauß, Jordi Levy [Com91], [SS94], [Lev96]

Date: September 1991, 1994, July 1996

Summary: Are context unification and linear second order unification decidable?

Context unification and linear second order unification are closely related, they both generalize string unification (which is known to be decidable, [Mak77]) and are special cases of second order unification (which is known to be undecidable, [Gol81]).

Context unification ([Com91], [SS94]) is unification of first-order terms with context variables that range over terms with one hole. Linear Second Order Unification is second-order unification where the domain of functions is restricted to λ -terms with exactly one occurrence of any bound variable (there can be several bound variables in contrast to context unification allowing for just one hole) Applications are

- solving membership constraints in completion of constraint rewriting ([Com98a])
- solving constraints occurring in Distributive Unification (Problem #38, [SS97])
- Extended Critical Pairs in Bi-Rewriting Systems ([LA96])
- Semantics of ellipses in natural language ([NPR97])
- One-Step Rewriting constraints ([NPR97])

Some special cases have been solved:

- Hubert Comon [Com98b] solved a special case where any occurrence of the same context variable is always applied to the same term,
- Manfred Schmidt-Schauß [SS94] (see also [SS97]) solved the case of so-called *stratified* context unification, where for any occurrence of the same second-order variable the string of second-order variables from this occurrence to the root of the containing term is the same,
- Jordi Levy [Lev96] (see also [NPR97]) showed that linear-second order unification is decidable when any variable has at most two occurrences.

- Manfred Schmidt-Schauß and Klaus Schulz [SSS99a] showed that solvability is decidable for systems of context equations containing only two context variables (having an arbitrary number of occurrences in the system) and an arbitrary number of first-order variables.

Progress towards a decidability proof along the lines of Makanin's proof for string-unification has been reported in [SSS98]. Levy and Villaret [LV00] show how to reduce linear second-order unification to context unification plus membership predicates in regular tree languages, and discuss a possible way of showing decidability of the latter. [LV02] shows that it is sufficient, both for linear 2nd-order and for context unification, to consider signatures consisting of an arbitrary number of constants and one binary function symbol.

Bibliography

- [Com91] Hubert Comon. Completion of rewrite systems with membership constraints. Rapport de Recherche 699, L.R.I., Université de Paris-Sud, September 1991.
- [Com98a] Hubert Comon. Completion of rewrite systems with membership constraints. Part I: Deduction rules. *Journal of Symbolic Computation*, 25:397–419, 1998.
- [Com98b] Hubert Comon. Completion of rewrite systems with membership constraints. Part II: Constraint solving. *Journal of Symbolic Computation*, 25:421–453, 1998.
- [Gol81] Warren D. Goldfarb. The undecidability of the second-order unification problem. *Theoretical Computer Science*, 13:225–230, 1981.
- [LA96] Jordi Levy and Jaume Agustí. Bi-rewriting systems. *Journal of Symbolic Computation*, 22(3):279–314, September 1996.
- [Lev96] Jordi Levy. Linear second-order unification. In Harald Ganzinger, editor, *7th International Conference on Rewriting Techniques and Applications*, volume 1103 of *Lecture Notes in Computer Science*, pages 332–346, New Brunswick, NJ, USA, July 1996. Springer-Verlag.
- [LV00] Jordi Levy and Mateu Villaret. Linear second-order unification and context unification with tree-regular constraints. In Leo Bachmair, editor, *Rewriting Techniques and Applications*, volume 1833 of *Lecture Notes in Computer Science*, pages 156–171, Norwich, UK, July 2000. Springer-Verlag.
- [LV02] Jordi Levy and Mateu Villaret. Currying second-order unification problems. In Sophie Tison, editor, *Rewriting Techniques and Applications*, volume 2378 of *Lecture Notes in Computer Science*, pages 326–339, Copenhagen, Denmark, July 2002. Springer-Verlag.

- [Mak77] G. S. Makanin. The problem of solvability of equations in a free semi-group. *Math. USSR Sbornik*, 32(2):129–198, 1977.
- [NPR97] Joachim Niehren, Manfred Pinkal, and Peter Ruhrberg. On equality up-to constraints over finite trees, context unification and one-step rewriting. In William McClune, editor, *14th International Conference on Automated Deduction*, volume 1249 of *Lecture Notes in Artificial Intelligence*, pages 34–48, Townsville, Australia, July 1997. Springer-Verlag.
- [SS94] Manfred Schmidt-Schauß. Unification of stratified second-order terms. Internal Report 12/94, Johann-Wolfgang-Goethe-Universität, Frankfurt, Germany, 1994.
- [SS97] Manfred Schmidt-Schauß. A unification algorithm for distributivity and a multiplicative unit. *Journal of Symbolic Computation*, 22(3):315–344, 1997.
- [SSS98] Manfred Schmidt-Schauß and Klaus Schulz. On the exponent of peridicity of minimal solutions of context equations. In Tobias Nipkow, editor, *9th International Conference on Rewriting Techniques and Applications*, volume 1379 of *Lecture Notes in Computer Science*, pages 61–75, Tsukuba, Japan, April 1998. Springer-Verlag.
- [SSS99a] Manfred Schmidt-Schauß and Klaus Schulz. Solvability of context unification with two context variables is decidable. In Harald Ganzinger, editor, *16th International Conference on Automated Deduction*, volume 1632 of *Lecture Notes in Artificial Intelligence*, pages 67–81, Trento, Italy, July 1999. Springer-Verlag. Complete version as [SSS99b].
- [SSS99b] Manfred Schmidt-Schauß and Klaus Schulz. Solvability of context unification with two context variables is decidable. CIS-Report 98-114, CIS, Universität München, München, Germany, 1999.

June 15, 2012