

Distributed Indexing of the Web Using Migrating Crawlers

Odysseas Papapetrou
Computer Science Department
University of Cyprus
cs98po1@ucy.ac.cy

Stavros Papastavrou
Computer Science Department
University of Cyprus
stavrosp@ucy.ac.cy

George Samaras
Computer Science Department
University of Cyprus
cssamara@ucy.ac.cy

1. INTRODUCTION

Indexing the Web has become a challenge due to its growing and dynamic nature. The directly accessible Web (also mentioned as surface Web) exceeds 2.5 billion documents while the indirect Web (dynamically generated documents) is almost three orders of magnitude larger [8]. Moreover, the Web is changing 40 per cent of its contents every month [6] while no search engine succeeds coverage of more than 16% of the estimated web size [7].

Web crawling (or traditional crawling) has been the dominant practice for Web indexing by popular search engines and research organizations since 1993, but despite the vast computational and network resources thrown into it, traditional crawling cannot effectively catch up with the dynamic Web. More specifically, the traditional crawling model fails for the following reasons:

- The task of processing the crawled data introduces a vast processing bottleneck at the search engine site.
- The attempt to download thousands of documents per second creates a network and a DNS lookup bottleneck.
- Documents are usually downloaded by the crawlers uncompressed increasing in this way the network bottleneck. In general, compression is not under full facilitation since it is independent from the crawling task and cannot be forced by the crawlers. In addition, crawlers download the entire contents of a document, including useless information such as scripting code and comments, which are rarely necessary for document indexing.

The absence of a scalable crawling method triggered some significant research in the past few years. Focused Crawling [2], was proposed as an alternative method but did not introduce any architectural innovations since it relied on the same centralized practices of traditional crawling. As a first attempt to improve the centralized nature of traditional crawling, a number of distributed methods have been proposed (Harvest [1], Grub [5]).

In this ongoing work, we introduce UCYMicra; a crawling system that utilizes concepts similar to those found in Mobile and distributed Crawling introduced in [3, 4]. UCYMicra extends these concepts and introduces new ones in order to build a more efficient model for distributed Web crawling, capable of keeping up with Web document changes in real time. UCYMicra proposes a complete distributed crawling strategy by utilizing Mobile Agents technology. The goals are (a) to minimize network utilization (b) to keep up with document changes by performing on-site monitoring, (c) to avoid unnecessary overloading of the Web servers by employing time realization, and (d) to be upgradeable at run time.

2. THE UCYMICRA CRAWLING SYSTEM

The driving force behind UCYMicra is the utilization of mobile agents that migrate from the search engine to the Web servers, and remain there to crawl, process, and monitor Web documents for updates. Since UCYMicra requires that a specific mobile agents platform be running at the Web Server to be crawled, it is currently running under a distributed voluntary academic environment spanning in a number of continents.

UCYMicra (Figure 1) consists of three subsystems, (a) the *Coordinator Subsystem*, (b) the *Mobile Agents Subsystem*, and (c) a *Public Search Engine* that executes user queries on the database maintained by the Coordinator subsystem.

The Coordinator Subsystem resides at the Search Engine site and is responsible of (a) maintaining the search database, (b) providing online registration for new Web sites to participate in UCYMicra, and (c) administering the *Mobile Agents Subsystem*. The Mobile Agents Subsystem is responsible for crawling the Web and consists of two categories of mobile agents, namely the *Migrating Crawlers* (or Mobile Crawlers) and the *Data Carriers*. Figure 2 shows UCYMicra at work.

As mentioned above, the core of the UCYMicra crawling system are the Java-based Migrating Crawlers. Powered by their inherent mobile capabilities, the Migrating Crawlers can perform the following tasks:

- (a) Be dispatched to a newly registered Web server that will participate in UCYMicra.
- (b) Crawling: A Migrating Crawler can perform a complete local crawling (either through HTTP or the file system).
- (c) Processing: Crawled documents are stripped down into keywords, and keywords are ranked based on their visual properties (font and color), position and occurrence frequency, in order to locally create a keyword index of the web server contents.
- (d) Compression: The index of the Web server contents is locally compressed to minimize transmission time between the Migrating Crawler and the Coordinator subsystem.
- (e) Data transmission: The compressed index is transmitted to the Coordinator subsystem by the Data Carriers. There, it is uncompressed and integrated into the search database. The choice of using mobile agents for data transmission over other network APIs (such as RMI, CORBA or sockets) is the utilization of their asynchronicity, flexibility and intelligence in order to ensure the seamless transmission of the data.
- (f) Monitoring: The Migrating Crawler can detect changes on the Web server contents. Detected changes are instantly processed, compressed and transmitted to the Coordinator subsystem.

